

Atrust All-in-One- A200A



1 Power Button

* Press to :

- a) Turn on the system.
- b) Resume from the suspend mode.

* Long press to **power off** the system.

2 LAN Port

It connects to a host server through a LAN switch.

3 USB 2.0 Port

It connects to USB device.

4 USB 2.0 Port

It connects to USB device.

5 DC IN

It connects to an AC adaptor.

6 Microphone Port

It connects to a microphone.

7 Headphone Port

It connects to a headphone or a speaker system.

8 USB 2.0 Port x 2

It connects to USB devices.

9 USB 2.0 Port x 2

It connects to USB devices.



Atrust All-in-One - A200A

System	
Processor	Freescale™ ARM® Quad Core 1.2GHz
Memory	
System memory	1GB (Manufacturing option: 2GB)
Flash memory	4GB
Display	
LCD Type/Resolution	23.6" LED Backlight / 1920 x 1080 pixels
I/O Interfaces	
I/O ports	6 x USB 2.0, 1 x Headphone port, 1 x Microphone port, 1 x RJ-45, 1 x DC IN
Networking	
Gigabit Ethernet	10/100/1000Mb
Dimensions / Weight	
Dimensions	(W) 569.6 x (D) 183.5 x (H) 412.3 mm (with stand)
Weight	4.85kg (approximate)
Environment	
Cooling	Fanless
Operating noise	No noise
Operating temperature	0°C ~ 35°C
Non-operating temperature	-30°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95%
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
AC Adaptor	19V, 65W, 3.42A
Software	
Operating system	Atrust OS
Protocols	Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™
Regulatory	
	CB, NRTL, FCC, CE, VCCI
Option	
	Internal Speaker

© 2017 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.atrustcorp.com.