





## w100 PCoIP Zero Client

Atrust w100 is a zero client based on hardware PCoIP engine of Teradici processor. It offers a rich computing experience that supports high resolution, full frame rate 3D graphics, HD video and audio, dual displays and USB peripheral connectivity. Atrust w100 zero client delivers the hardware acceleration user experience to task workers as well as power users in a truly uncompromised computing environment.

- 1 Power LED**  
Indicates the status of power.
- 2 Power Button**  
Press to turn on the client.
- 3 Microphone Port**  
Connects to a microphone.
- 4 Headphone Port**  
Connects to a headphone or a speaker system.
- 5 USB Port**  
Connects to a USB device.
- 6 Kensington Lock Slot**  
Attach the w100 to a permanent object with the Kensington slot and a security cable.
- 7 DVI-D Port**  
Connects to a monitor.
- 8 DVI-I Port**  
Connects to a monitor.
- 9 LAN Port**  
Connects to a host server through a LAN switch.
- 10 USB Port**  
Connects to keyboard or mouse.
- 11 USB Port**  
Connects to keyboard or mouse.
- 12 DC IN**  
Connects to an AC adaptor.



## Atrust w100 (VMware PCoIP)

<b>System</b>	
Processor	Teradici® TERA2321
<b>Memory</b>	
System memory	512MB
<b>Graphics</b>	
Max resolution	2x 1920 x 1200 1x 2560 x 1600 (with special dual-link DVI cable--option)* <small>*A special dual-link DVI cable is required that connects to the two DVI ports on the w100 and outputs a dual-link DVI signal to a DVI monitor capable of supporting 2560x1600 resolution.</small>
<b>I/O Interfaces</b>	
I/O ports	Front: 2 x USB, 1 x Headphone port, 1 x Microphone port, Rear: 1 x DVI-I, 1 x DVI-D, 1 x RJ45, 1 x DC IN, 1 x Kensington lock slot
<b>Networking</b>	
Ethernet	10/100/1000Mb
<b>Dimensions / Weight</b>	
Dimensions	(W) 39.5 x (D) 103 x (H) 143 mm
Weight	362g (approximate)
<b>Environment</b>	
Operating temperature	0°C ~ 35°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
<b>Power</b>	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
Rated output current (max)	3A
Output voltage	+5V DC
<b>Software</b>	
Protocols	VMware® Horizon View™
<b>Regulatory</b>	CB, NRTL, FCC, CE, VCCI, BSMI, CCC, Energy Star

© 2017 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit [www.atrustcorp.com](http://www.atrustcorp.com).