




Thin Client

Atrust t35 (Raspberry Pi® 4)



1 Power Button

2 DC IN

3 Micro HDMI Port x 2

4 Audio Out

5 Kensington Lock Slot

6 USB 2.0 Port x 2

7 USB 3.0 Port x 2

8 LAN Port

Atrust t35 is a Linux-based thin client device especially designed for a client/server computing environment. Developed by Atrust, the ACS (Atrust Client Setup) software is also built in to help effective management of t35. With the support of Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™ and VMware® Horizon View™, t35 can be used to create virtual and session-based desktop experiences from many remote desktop capable operating systems. t35 offers a rich computing experience where applications look, feel, and behave as local devices, including high-definition multimedia content.

Atrust t35 Features

- ▼ Dual Micro HDMI Display Ports
- ▼ Integrated with Atrust Device Manager software
- ▼ Broadcom BCM2711 Quad Core 1.5GHz 64-bit CPU
- ▼ Support for WiFi
- ▼ Low Power Consumption

Atrust t35

System	t35
Processor	Broadcom BCM2711 Quad Core 1.5GHz 64-bit CPU
Memory	
System memory	2GB (Manufacturing option : 4GB)
Flash memory	16GB
Graphics	
Maximum resolution	Atrust recommendation: Citrix ICA/HDX: 1920 x 1080 @ 60 Hz Microsoft RDP with RemoteFX: 2560 x 1600 @ 60 Hz VMware Horizon View: 2560 x 1600 @ 60 Hz
I/O Interfaces	
I/O ports	Side: 2 x USB 3.0, 2 x USB 2.0 (Maximum total USB peripheral current draw is 1.2A), 1 x RJ-45 Rear: 2 x Micro HDMI, 1 x Audio Out, 1 x DC IN
Networking	
Ethernet	Gigabit ethernet
WiFi	802.11b/g/n/ac wireless LAN
Dimensions / Weight	
Dimensions	(W) 105.3 x (D) 76 x (H) 34 mm
Weight	134g (approximate)
Environment	
Cooling	Fan
Operating temperature	0°C ~ 35°C
Non-operating temperature	-20°C ~ 60°C
Operating humidity (Rh)	20% ~ 80% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
Rated output current (max)	3A
Output voltage	5V
Software	
Operating system	Atrust OS
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocol	Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™(Blast Extreme)
Manufacturing option	VESA Mount, Micro HDMI Cable

©2020 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.atrustcorp.com.